

MULTIFLEX 512®-PUR UL/CSA special cable

for drag chains, 80°C, 600V, two approvals control cable



Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
21595	2 x 1,5	16	7,6	29,0	70,0
21596	3 G 1,5	16	8,1	43,0	90,0
21597	4 G 1,5	16	8,7	58,0	106,0
21598	5 G 1,5	16	9,7	72,0	145,0
21599	7 G 1,5	16	11,3	101,0	205,0
21600	12 G 1,5	16	13,8	173,0	320,0
21601	18 G 1,5	16	16,3	259,0	465,0
21602	20 G 1,5	16	17,3	288,0	510,0
21603	25 G 1,5	16	19,7	360,0	650,0
21604	30 G 1,5	16	20,3	432,0	750,0
21605	36 G 1,5	16	22,2	518,0	880,0
21606	42 G 1,5	16	24,0	628,0	1209,0
21607	50 G 1,5	16	26,2	749,0	1449,0
21608	61 G 1,5	16	28,9	912,0	1712,0
21609	2 x 2,5	14	9,2	48,0	115,0
21610	3 G 2,5	14	9,7	72,0	162,0
21611	4 G 2,5	14	10,5	96,0	196,0
21612	5 G 2,5	14	11,6	120,0	230,0
21613	7 G 2,5	14	13,8	168,0	312,0
21614	12 G 2,5	14	16,9	288,0	532,0
21615	18 G 2,5	14	20,0	432,0	762,0
21616	20 G 2,5	14	21,2	480,0	858,0
21617	25 G 2,5	14	24,3	600,0	998,0

Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
21618	4 G 4	12	13,1	154,0	283,0
21619	5 G 4	12	14,2	192,0	349,0
21620	7 G 4	12	17,1	269,0	498,0
21621	4 G 6	10	14,3	230,0	432,0
21622	5 G 6	10	15,8	288,0	529,0
21623	7 G 6	10	19,2	403,0	782,0
21624	4 G 10	8	18,4	384,0	685,0
21625	5 G 10	8	20,7	480,0	817,0
21626	7 G 10	8	24,7	672,0	1023,0
21627	4 G 16	6	21,3	614,0	1042,0
21628	5 G 16	6	23,8	768,0	1292,0
21629	7 G 16	6	28,6	1075,0	1709,0

Dimensions and specifications may be changed without prior notice.



Our Service on the Internet:

Program

You will receive a very detailed and exact overview of our broad spectrum of cables, wires, accessories and data, network and bus technics as soon as HELUROBOTICS. The technical documentation is extensive and leaves no questions unanswered.

www.helukabel.de