

JZ-600 PUR tear and coolant resistant, 0,6/1kV



Part No. Colour black	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
28272	2 x 2,5	14	9,5	48,0	170,0
28273	3 G 2,5	14	10,0	72,0	181,0
28274	4 G 2,5	14	11,1	96,0	203,0
28275	5 G 2,5	14	12,4	120,0	251,0
28276	7 G 2,5	14	15,0	168,0	330,0
28277	12 G 2,5	14	18,4	288,0	553,0
28278	18 G 2,5	14	22,0	432,0	795,0
28279	25 G 2,5	14	26,9	600,0	1110,0
28280	2 x 4	12	11,4	77,0	190,0
28281	3 G 4	12	12,3	115,0	235,0
28282	4 G 4	12	13,8	154,0	310,0
28283	5 G 4	12	15,3	192,0	410,0
28284	7 G 4	12	16,8	269,0	540,0
28285	12 G 4	12	22,9	461,0	860,0
28286	3 G 6	10	14,1	173,0	370,0
28287	4 G 6	10	15,6	230,0	450,0
28288	5 G 6	10	17,3	288,0	650,0
28289	7 G 6	10	19,3	403,0	860,0
28290	3 G 10	8	16,5	288,0	660,0
28291	4 G 10	8	18,4	384,0	790,0
28292	5 G 10	8	20,5	480,0	960,0
28293	7 G 10	8	22,5	672,0	1300,0
28294	3 G 16	6	19,6	461,0	709,0
28295	4 G 16	6	21,7	614,0	1114,0
28296	5 G 16	6	24,2	768,0	1620,0
28297	7 G 16	6	25,8	1075,0	1900,0
28298	3 G 25	4	24,0	720,0	1450,0
28299	4 G 25	4	26,9	960,0	1600,0
28300	5 G 25	4	29,3	1200,0	2050,0
28301	7 G 25	4	32,6	1680,0	2900,0

Part No. Colour grey	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
28337	2 x 2,5	14	9,5	48,0	170,0
28338	3 G 2,5	14	10,0	72,0	181,0
28339	4 G 2,5	14	11,1	96,0	203,0
28340	5 G 2,5	14	12,4	120,0	251,0
28341	7 G 2,5	14	15,0	168,0	330,0
28342	12 G 2,5	14	18,4	288,0	553,0
28343	18 G 2,5	14	22,0	432,0	795,0
28344	25 G 2,5	14	26,9	600,0	1110,0
28345	2 x 4	12	11,4	77,0	190,0
28346	3 G 4	12	12,3	115,0	235,0
28347	4 G 4	12	13,8	154,0	310,0
28348	5 G 4	12	15,3	192,0	410,0
28349	7 G 4	12	16,8	269,0	540,0
28350	12 G 4	12	22,9	461,0	860,0
28351	3 G 6	10	14,1	173,0	370,0
28352	4 G 6	10	15,6	230,0	450,0
28353	5 G 6	10	17,3	288,0	650,0
28354	7 G 6	10	19,3	403,0	860,0
28355	3 G 10	8	16,5	288,0	660,0
28356	4 G 10	8	18,4	384,0	790,0
28357	5 G 10	8	20,5	480,0	960,0
28358	7 G 10	8	22,5	672,0	1300,0
28359	3 G 16	6	19,6	461,0	709,0
28360	4 G 16	6	21,7	614,0	1114,0
28361	5 G 16	6	24,2	768,0	1620,0
28362	7 G 16	6	25,8	1075,0	1900,0
28363	3 G 25	4	24,0	720,0	1450,0
28364	4 G 25	4	26,9	960,0	1600,0
28365	5 G 25	4	29,3	1200,0	2050,0
28366	7 G 25	4	32,6	1680,0	2900,0

Dimensions and specifications may be changed without prior notice.

Approach

To get in touch with us, we kindly ask you to fill out the following form. Your data will be handled confidentially and will not be passed to any third party.

We will get in touch with you as soon as possible!

Customer no.

Company

Salutation ☐ Mr. ☐ Ms.

First name

Last name

Postal Code/City

Country

Phone

Email-address

Method of contact

Product range ☐ Cables & Wires ☐ Special Cables

Appointment date (dd/mm/yy)

Your message

Our Service on the Internet:

Making contact

Your direct line to us.
Here you can enter your most important
contact data as well as the product area,
also any information you would like.
We will call you back as soon as possible.

www.helukabel.de