

# JZ-600-Y-CY flexible, number coded, 0,6/1kV, Cu screened

## EMC-preferred type



Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
11599	4 G 6	18,7	319,0	731,0	10
11600	5 G 6	20,7	421,0	1105,0	10
11601	7 G 6	23,0	561,0	1465,0	10
11602	2 x 10	18,4	265,0	845,0	8
11603	3 G 10	19,6	371,0	1125,0	8
11604	4 G 10	21,9	576,0	1345,0	8
11605	5 G 10	24,1	620,0	1635,0	8
11606	7 G 10	26,8	842,0	2210,0	8
11607	2 x 16	22,0	407,0	1150,0	6
11608	3 G 16	23,5	540,0	1395,0	6
11609	4 G 16	26,4	807,0	1870,0	6
11610	5 G 16	28,8	1394,0	2720,0	6
11611	7 G 16	31,9	1605,0	3213,0	6
11612	3 G 25	28,0	820,0	2465,0	4
11613	4 G 25	32,5	1169,0	2750,0	4
11614	5 G 25	35,7	1850,0	3490,0	4
11615	7 G 25	39,0	2140,0	4980,0	4
11616	3 G 35	32,7	1344,0	3230,0	2
11617	4 G 35	35,7	1686,0	4100,0	2
11618	5 G 35	40,0	2023,0	4950,0	2

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
11619	3 G 50	36,5	1460,0	4590,0	1
11620	4 G 50	41,1	2374,0	5780,0	1
11621	5 G 50	44,6	2890,0	7210,0	1
11622	3 G 70	44,1	2730,0	5610,0	2/0
11623	4 G 70	48,0	3257,0	7480,0	2/0
11624	5 G 70	52,5	4100,0	9390,0	2/0
11625	3 G 95	46,6	3236,0	8585,0	3/0
11626	4 G 95	51,2	4050,0	10220,0	3/0
11627	5 G 95	58,4	5264,0	13800,0	3/0
11628	3 G 120	51,5	4540,0	11105,0	4/0
11629	4 G 120	56,0	5231,0	13750,0	4/0
13137	4 G 150	63,8	6794,0	15990,0	300 kcmil
13147	4 G 185	71,0	8104,0	18470,0	350 kcmil

Dimensions and specifications may be changed without prior notice.



## Our Service on the Internet:

### Program

You will receive a very detailed and exact overview of our broad spectrum of cables, wires, accessories and data, network and bus technics as soon as HELUROBOTICS. The technical documentation is extensive and leaves no questions unanswered.

[www.helukabel.de](http://www.helukabel.de)