

JZ-602-C-PUR screened two approvals control cable, 80°C, 600V, EMC-preferred type



Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
12614	3 G 35	2	33,8	1501,0	2701,0
12615	4 G 35	2	37,7	1889,0	3277,0
12616	5 G 35	2	41,5	2532,0	4530,0
12617	4 G 50	1	41,8	2210,0	3370,0

Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
12618	4 G 70	2/0	47,0	2915,0	4630,0
12619	4 G 95	3/0	51,0	3920,0	6114,0
12620	4 G 120	4/0	58,0	5097,0	7417,0

Dimensions and specifications may be changed without prior notice.

Drag and guidance chains

EFK Series open:

10.1 / 14 / 18.1 / 18.2 / 35 / 3000 / 44 / 52.2 / 62.2

EFK Series closed: 25G / 36G

Chain brackets / separators

Filing systems / insertion aid

Assembly instruction

Selection table / Cables in drag chains



**You can find drag and guidance chains in our catalogue cable accessories.
Request it now at www.helukabel.de**