

MULTIFLEX 512®-PUR special cable for drag chains, halogen-free



Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
22523	2 x 1	6,9	19,2	55,0	17
22524	3 G 1	7,4	29,0	70,0	17
22525	4 G 1	8,0	38,0	86,0	17
22526	5 G 1	8,7	48,0	102,0	17
22527	7 G 1	10,2	67,0	143,0	17
22528	12 G 1	12,6	115,0	225,0	17
22529	18 G 1	14,8	173,0	334,0	17
22530	20 G 1	15,8	192,0	370,0	17
22531	25 G 1	17,8	240,0	460,0	17
22532	30 G 1	18,5	288,0	530,0	17
22533	36 G 1	20,1	346,0	625,0	17
22878	41 G 1	21,2	410,0	779,0	17
22879	50 G 1	24,0	498,0	953,0	17
22880	65 G 1	27,2	650,0	1205,0	17
22534	2 x 1,5	7,6	29,0	70,0	16
22535	3 G 1,5	8,1	43,0	90,0	16
22536	4 G 1,5	8,7	58,0	106,0	16
22537	5 G 1,5	9,7	72,0	145,0	16
22538	7 G 1,5	11,3	101,0	205,0	16
22539	12 G 1,5	13,8	173,0	320,0	16
22540	18 G 1,5	16,3	259,0	465,0	16
22541	20 G 1,5	17,3	288,0	510,0	16
22542	25 G 1,5	19,7	360,0	650,0	16
22543	30 G 1,5	20,3	432,0	750,0	16
22544	36 G 1,5	22,2	518,0	880,0	16
22881	42 G 1,5	24,0	628,0	1209,0	16
22882	50 G 1,5	26,2	749,0	1449,0	16
22883	61 G 1,5	28,9	912,0	1712,0	16

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
22545	2 x 2,5	9,2	48,0	115,0	14
22546	3 G 2,5	9,7	72,0	162,0	14
22547	4 G 2,5	10,5	96,0	196,0	14
22548	5 G 2,5	11,6	120,0	230,0	14
22549	7 G 2,5	13,8	168,0	312,0	14
22550	12 G 2,5	16,9	288,0	532,0	14
22551	18 G 2,5	20,0	432,0	762,0	14
22552	20 G 2,5	21,2	480,0	858,0	14
22553	25 G 2,5	24,3	600,0	998,0	14
22554	4 G 4	13,1	154,0	283,0	12
22555	5 G 4	14,2	192,0	349,0	12
22556	7 G 4	17,1	269,0	498,0	12
22557	4 G 6	14,3	230,0	432,0	10
22558	5 G 6	15,8	288,0	529,0	10
22559	7 G 6	19,2	403,0	782,0	10
22560	4 G 10	18,4	384,0	685,0	8
22561	5 G 10	20,7	480,0	817,0	8
22562	7 G 10	24,7	672,0	1023,0	8
22563	4 G 16	21,3	614,0	1042,0	6
22564	5 G 16	23,8	768,0	1292,0	6
22565	7 G 16	28,6	1075,0	1709,0	6

Dimensions and specifications may be changed without prior notice.

A

To be able to provide information on the service life and in line with our certification to DIN EN ISO 9001:2000, we document the realistic testing of our cables suitable for use in drag chains.

HELUKABEL GMBH						
MULTIFLEX 512 PUR / C - PUR						
Art. Nr.	Adresszahl x Nennquerschnitt mm	Außendurchmesser mm	geschliffen	Mindestbiegeradius	PA-W	Typische Lebensdauer
22516	700,5	8,10	nein	5rd	3321	1.250.000
22519	200,75	13,50	nein	5rd	298	1.250.000
22507	1800,5	11,50	nein	5rd	2740	1.250.000
22527	751	10,20	nein	5rd	3782	1.250.000
22518	18070,5	12,90	nein	5rd	3444	1.250.000
22550	1202,5	16,90	nein	5rd	4173	1.250.000
22565	7516	28,60	nein	5rd	4073	1.250.000
22559	756	19,20	ja	7,5rd	408	1.250.000
22579	2500,5	17,00	ja	7,5rd	2817	1.250.000
22588	1800,75	16,30	ja	7,5rd	438	1.250.000
22578	2000,5	15,40	ja	7,5rd	2171	1.250.000
22576	2000,5	9,00	ja	7,5rd	2148	1.250.000
22573	400,5	9,30	ja	7,5rd	2117	1.250.000