

MULTISPEED® 500-C-PUR UL/CSA safety

against high bending in drag chain systems, low torsion, halogen-free,
EMC-preferred type



Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24427	2 x 1	18	7,1	50,0	120,0
24428	3 G 1	18	7,7	59,0	140,0
24429	4 G 1	18	8,3	70,0	167,0
24430	5 G 1	18	9,1	84,0	201,0
24431	7 G 1	18	13,3	106,0	256,0
24432	12 G 1	18	14,4	174,0	417,0
24433	18 G 1	18	17,3	240,0	557,0
24434	25 G 1	18	19,4	332,0	766,0

Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
24435	3 G 1,5	16	8,6	75,0	170,0
24436	4 G 1,5	16	9,4	90,0	204,0
24437	5 G 1,5	16	10,4	108,0	236,0
24438	7 G 1,5	16	15,2	157,0	309,0
24439	12 G 1,5	16	16,6	240,0	509,0
24440	18 G 1,5	16	20,3	355,0	718,0
24441	25 G 1,5	16	22,6	448,0	944,0
24442	4 G 2,5	14	12,3	134,0	280,0
24443	5 G 2,5	14	12,2	175,0	346,0
24444	7 G 2,5	14	14,0	229,0	410,0

Dimensions and specifications may be changed without prior notice.

Isolation and heatshrink sleeves

Braided hoses

PVC insulation tubes black / coloured

Silikon insulation tubes

PVC shrink-on tubes black / coloured

Polyolefin shrink-on tubes black / coloured

Shrink-on tubes with inner wall hot melt adhesive

End caps



You can find isolation and heatshrink sleeves in our catalogue cable accessories.
Request it now at www.helukabel.de