

TOPSERV® 155 / 156 PUR, high flexible drag chain servo cable, 0,6/1kV, low capacitance, halogen-free



TOPSERV® 155 (1 control pair) EMC

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
79566	(4 x 10,0 + (2 x 1,0))	18,0	574,0	853,0	8
700505	(4 x 10,0 + (2 x 1,5))	18,0	584,0	863,0	8
79567	(4 x 16,0 + (2 x 1,0))	21,8	815,0	1194,0	6
700506	(4 x 16,0 + (2 x 1,5))	21,8	825,0	1204,0	6
79568	(4 x 25,0 + (2 x 1,0))	26,7	1273,0	1499,0	4
700507	(4 x 25,0 + (2 x 1,5))	26,7	1283,0	1509,0	4
79569	(4 x 35,0 + (2 x 1,0))	30,8	1840,0	1992,0	2
700508	(4 x 35,0 + (2 x 1,5))	30,8	1850,0	2002,0	2
79570	(4 x 50,0 + (2 x 1,0))	34,7	2530,0	2880,0	1
700509	(4 x 50,0 + (2 x 1,5))	34,7	2540,0	2890,0	1

TOPSERV® 156 (2 and 4 respectively control pairs) EMC

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
700514	(4 x 10,0 + 2 x (2 x 1,5))	18,8	619,0	915,0	8
79576	(4 x 16,0 + 2 x (2 x 1,0))	21,8	894,0	1225,0	6
700515	(4 x 16,0 + 2 x (2 x 1,5))	21,8	904,0	1235,0	6
79577	(4 x 25,0 + 2 x (2 x 1,0))	26,7	1313,0	1584,0	4
700516	(4 x 25,0 + 2 x (2 x 1,5))	26,7	1323,0	1594,0	4
79578	(4 x 35,0 + 2 x (2 x 1,0))	30,8	1911,0	2185,0	2
700517	(4 x 35,0 + 2 x (2 x 1,5))	30,8	1921,0	2195,0	2
79579	(4 x 50,0 + 2 x (2 x 1,0))	34,7	2574,0	2974,0	1
700518	(4 x 50,0 + 2 x (2 x 1,5))	34,7	2584,0	2984,0	1

Dimensions and specifications may be changed without prior notice.

B

Terminals and cable lugs

- Terminals
- Assortment box
- Insulated terminal ends
- Applied pressure lugs
- Tubular cable lugs
- Pin lugs
- Link cable lugs
- Press connecting connectors



You can find terminals and cable lugs in our catalogue cable accessories. Request it now at www.helukabel.de