

TOPFLEX® -EMV-UV-2YSLCYK-J for power supply connections to frequency converters, double screened, 0,6/1kV

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Mutual capacitance core/core ca. nF/km	Mutual capacitance core/shield ca. nF/km	Coupling resistance with 1 MHz Ohm/km	Coupling resistance with 30 MHz Ohm/km	Power ratings **) with 3 loaded cores in Ampère	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
22240	(4 x 25,0)	27,0	120,0	210,0	4,0	95,0	108,0	1236	1860,0	4
22241	(4 x 35,0)	30,7	150,0	260,0	3,0	85,0	135,0	1662	2610,0	2
22242	(4 x 50,0)	36,1	190,0	320,0	2,0	40,0	168,0	2345	2950,0	1
22243	(4 x 70,0)	42,3	190,0	320,0	2,0	45,0	207,0	3196	3950,0	2/0
22244	(4 x 95,0)	47,7	250,0	410,0	1,0	50,0	250,0	4316	5300,0	3/0
22245	(4 x 120,0)	51,9					292,0	5435	6600,0	4/0
22246	(4 x 150,0)	57,5					335,0	6394	7040,0	300 kcmil
22247	(4 x 185,0)	61,1					382,0	7639	8580,0	350 kcmil

Dimensions and specifications may be changed without prior notice.

**) The current carrying capacity for permanent operation at ambient temperature of 30°C. For deviating ambient temperatures the conversion factors should be used and for further see the indication in DIN VDE 0298 part 4.

Tools

Box spanners
Cable binder tools
Crimp tools
Cutting tools
Assembly tools
Stripping tools
HELUstar pressing tools and accessories

You can find tools in our catalogue cable accessories.
Request it now at www.helukabel.de

