

TOPSERV® 112 / 123 Siemens Standard 6FX 8008- high flexible drag chain servo cable 0,6/1kV, PUR, VDE-Reg.-No., halogen-free



TOPSERV® 112 (1 control pair) EMC

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
74435	(4 x 10,0 + (2 x 1,0))	21,6	574,0	853,0	8
78942	(4 x 10,0 + (2 x 1,5))	21,6	584,0	865,0	8
74436	(4 x 16,0 + (2 x 1,0))	24,8	815,0	1194,0	6
75952	(4 x 16,0 + (2 x 1,5))	24,8	825,0	1205,0	6
74437	(4 x 25,0 + (2 x 1,0))	26,5	1273,0	1499,0	4
75953	(4 x 25,0 + (2 x 1,5))	26,5	1283,0	1510,0	4
74438	(4 x 35,0 + (2 x 1,0))	32,0	1840,0	1992,0	2
75954	(4 x 35,0 + (2 x 1,5))	32,0	1850,0	2005,0	2
74439	(4 x 50,0 + (2 x 1,0))	35,8	2530,0	2890,0	1
75955	(4 x 50,0 + (2 x 1,5))	35,8	2540,0	2890,0	1

TOPSERV® 123 (2 control pairs) EMC

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
74444	(4 x 10,0 + 2 x (2 x 1,0))	22,4	609,0	905,0	8
78947	(4 x 10,0 + 2 x (2 x 1,5))	22,4	619,0	915,0	8
74445	(4 x 16,0 + 2 x (2 x 1,0))	25,2	894,0	1225,0	6
75982	(4 x 16,0 + 2 x (2 x 1,5))	25,2	904,0	1225,0	6
74446	(4 x 25,0 + 2 x (2 x 1,0))	28,0	1313,0	1584,0	4
75983	(4 x 25,0 + 2 x (2 x 1,5))	28,0	1323,0	1595,0	4
74447	(4 x 35,0 + 2 x (2 x 1,0))	31,0	1611,0	2185,0	2
75984	(4 x 35,0 + 2 x (2 x 1,5))	31,0	1621,0	2196,0	2
74448	(4 x 50,0 + 2 x (2 x 1,0))	36,0	2574,0	2974,0	1
75985	(4 x 50,0 + 2 x (2 x 1,5))	36,0	2585,0	2985,0	1

Dimensions and specifications may be changed without prior notice.

Identification and marking

- Identification rings
- Cable marker
- Fixing accessories



You can find identification and marking in our catalogue cable accessories.
Request it now at www.helukabel.de