


PAAR-TRONIC-CY-CY (LiYCY-CY) EMC-preferred type

Part No.	No.pairs x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
21077	2 x 2 x 0,25	9,5	62,0	125,0	24
21078	3 x 2 x 0,25	10,0	78,2	140,0	24
21079	4 x 2 x 0,25	12,0	124,1	205,0	24
21080	5 x 2 x 0,25	12,1	137,6	230,0	24
21081	6 x 2 x 0,25	13,0	148,1	275,0	24
21082	7 x 2 x 0,25	16,0	159,1	295,0	24
21083	8 x 2 x 0,25	17,0	178,7	330,0	24
21084	10 x 2 x 0,25	17,2	213,9	420,0	24
21085	12 x 2 x 0,25	17,5	238,3	465,0	24
21086	16 x 2 x 0,25	22,0	291,4	590,0	24
21087	20 x 2 x 0,25	22,6	325,0	620,0	24
21088	24 x 2 x 0,25	27,5	367,5	690,0	24
21089	32 x 2 x 0,25	29,8	588,0	785,0	24
21090	48 x 2 x 0,25	34,5	840,5	970,0	24
21091	2 x 2 x 0,34	10,1	73,1	139,0	22
21092	3 x 2 x 0,34	11,0	88,1	157,0	22
21093	4 x 2 x 0,34	12,4	137,2	213,0	22
21094	6 x 2 x 0,34	14,5	174,8	308,0	22
21095	8 x 2 x 0,34	17,6	247,2	385,0	22
21096	10 x 2 x 0,34	17,6	288,7	433,0	22
21097	12 x 2 x 0,34	18,5	321,0	495,0	22
21098	14 x 2 x 0,34	20,7	388,4	600,0	22
21099	16 x 2 x 0,34	22,5	425,5	637,0	22
21100	24 x 2 x 0,34	28,0	577,1	781,0	22

Part No.	No.pairs x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
21101	2 x 2 x 0,5	10,8	83,1	143,0	20
21102	3 x 2 x 0,5	11,4	106,4	179,0	20
21103	4 x 2 x 0,5	13,0	158,0	241,0	20
21104	6 x 2 x 0,5	14,9	201,4	319,0	20
21105	8 x 2 x 0,5	18,8	311,5	441,0	20
21106	10 x 2 x 0,5	18,0	334,5	464,0	20
21107	12 x 2 x 0,5	20,1	394,1	529,0	20
21108	14 x 2 x 0,5	21,6	446,0	641,0	20
21109	16 x 2 x 0,5	23,8	501,2	694,0	20
21110	24 x 2 x 0,5	28,4	712,4	950,0	20

Dimensions and specifications may be changed without prior notice.



Our Service on the Internet:

Catalogue, brochure and flyer requests

Here you can request catalogues, brochures and flyers or download them immediately as pdf-documents. Just click and order.

www.helukabel.de