

Y-CY-JB flexible, CU-screened, transparent, EMC-preferred type



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
16153	4 G 16	22,6	1240,0	1380,0	6
16154	5 G 16	25,2	1390,0	1553,0	6
16469	4 G 25	28,9	1310,0	1890,0	4
16155	5 G 25	31,8	1840,0	2270,0	4
16470	4 G 35	32,2	1610,0	2390,0	2
16156	5 G 35	36,4	2015,0	2885,0	2
16471	4 G 50	38,2	2220,0	3315,0	1
16119	5 G 50	43,0	2880,0	4150,0	1

Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
16472	4 G 70	46,8	3090,0	4600,0	2/0
16473	4 G 95	51,0	4060,0	6060,0	3/0
16474	4 G 120	56,0	5150,0	7315,0	4/0
16247	4 G 150	63,5	6740,0	9340,0	300 kcmil
16319	4 G 185	68,0	8418,0	11120,0	350 kcmil

Dimensions and specifications may be changed without prior notice.

C



Standardised process control and visualisation of an extrusion system at our Windsbach factory.