

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
23007	2 x 1	6,6	19,0	59,0	17
23008	3 G 1	7,4	29,0	77,0	17
23009	4 G 1	8,0	38,0	94,0	17
23010	5 G 1	8,8	48,0	115,0	17
23011	6 G 1	9,5	58,0	134,0	17
23012	7 G 1	9,5	67,0	144,0	17
23133	8 G 1	10,4	76,7	175,0	17
23134	10 G 1	11,3	96,1	216,0	17
23135	12 G 1	11,5	115,2	231,0	17
23136	16 G 1	13,1	153,5	302,0	17
23137	18 G 1	13,8	172,9	340,0	17
23138	25 G 1	16,2	240,0	431,0	17
23013	2 x 1,5	7,6	29,0	81,0	16
23014	3 G 1,5	8,0	43,0	98,0	16
23015	4 G 1,5	8,8	58,0	122,0	16
23016	5 G 1,5	9,6	72,0	147,0	16
23017	6 G 1,5	10,4	86,0	173,0	16
23018	7 G 1,5	10,4	101,0	187,0	16
23019	8 G 1,5	11,6	114,0	213,0	16
23020	10 G 1,5	13,6	116,0	263,0	16
23021	12 G 1,5	14,6	173,0	314,0	16
23022	14 G 1,5	15,4	202,0	379,0	16
23023	16 G 1,5	16,7	231,0	445,0	16
23024	18 G 1,5	17,6	260,0	506,0	16
23025	20 G 1,5	18,2	288,0	566,0	16
23026	24 G 1,5	20,0	346,0	722,0	16
23027	2 x 2,5	9,2	48,0	134,0	14
23028	3 G 2,5	9,7	72,0	152,0	14
23029	4 G 2,5	10,6	96,0	188,0	14
23030	5 G 2,5	11,6	120,0	228,0	14
23139	6 G 2,5	12,9	144,0	304,0	14
23032	7 G 2,5	13,0	168,0	320,0	14
23140	8 G 2,5	14,9	192,2	373,0	14
23141	10 G 2,5	16,5	240,1	450,0	14
23033	12 G 2,5	17,8	288,0	502,0	14
23142	16 G 2,5	19,1	384,0	659,0	14
23143	18 G 2,5	20,0	432,2	761,0	14
23144	25 G 2,5	24,5	600,0	1007,0	14

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
23034	2 x 4	10,8	77,0	180,0	12
23035	3 G 4	11,4	115,0	224,0	12
23036	4 G 4	13,1	154,0	295,0	12
23037	5 G 4	14,4	192,0	359,0	12
23039	7 G 4	16,2	269,0	479,0	12
23040	2 x 6	13,4	115,0	274,0	10
23041	3 G 6	14,2	173,0	338,0	10
23042	4 G 6	16,2	230,0	441,0	10
23043	5 G 6	17,7	288,0	535,0	10
23045	7 G 6	19,2	403,0	685,0	10
23046	2 x 10	17,6	192,0	400,0	8
23047	3 G 10	18,7	288,0	620,0	8
23048	4 G 10	20,4	384,0	707,0	8
23049	5 G 10	22,5	480,0	900,0	8
23145	7 G 10	24,4	672,2	1151,0	8
23050	2 x 16	20,4	308,0	400,0	6
23051	3 G 16	22,0	462,0	500,0	6
23052	4 G 16	24,3	616,0	714,0	6
23053	5 G 16	26,7	770,0	850,0	6
23146	7 G 16	27,6	1075,3	1682,0	6
23054	2 x 25	24,6	480,0	700,0	4
23055	3 G 25	26,2	720,0	1100,0	4
23056	4 G 25	31,8	960,0	1500,0	4
23057	2 x 35	28,2	672,0	1100,0	2
23058	3 G 35	29,9	1008,0	1500,0	2
23059	4 G 35	32,8	1344,0	2100,0	2

Dimensions and specifications may be changed without prior notice.

Approach

To get in touch with us, we kindly ask you to fill out the following form. Your data will be handled confidentially and will not be passed to any third party.

We will get in touch with you as soon as possible!

Customer no.

Company

Salutation ☐ Mr. ☐ Ms.

First name

Last name

Postal Code/City

Country

Phone

Email-address

Method of contact

Product range: ☐ Cables & Wires ☐ Special Cables

Appointment date (dd/mm/yy):

Your message:

Our Service on the Internet:

Making contact

Your direct line to us. Here you can enter your most important contact data as well as the product area, also any information you would like. We will call you back as soon as possible.

www.helukabel.de