

JZ 604 TC TRAY CABLE PVC power cable, 90°C, 600V




Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
69715	3 G 16	6	21,0	461,0	651,0
69716	4 G 16	6	23,9	614,0	869,0
69717	5 G 16	6	26,3	768,0	1117,0
69718	7 G 16	6	28,8	1075,0	1364,0
69719	3 G 25	4	24,9	720,0	1090,0
69720	4 G 25	4	27,2	960,0	1421,0
69721	5 G 25	4	30,3	1200,0	1611,0
69722	7 G 25	4	33,1	1680,0	1943,0
69723	3 G 35	2	27,1	1008,0	1734,0
69724	4 G 35	2	29,8	1344,0	2011,0
69725	5 G 35	2	33,0	1680,0	2347,0
69726	3 G 50	1	33,2	1440,0	2041,0
69727	4 G 50	1	36,7	1920,0	2539,0
69728	5 G 50	1	41,5	2400,0	2894,0

Part No.	No. cores x cross-sec. mm²	AWG-no.	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km
69729	3 G 70	2/0	37,6	2016,0	2831,0
69730	4 G 70	2/0	42,0	2688,0	3494,0
69731	5 G 70	2/0	47,6	3360,0	4260,0
69732	3 G 95	3/0	41,8	2736,0	5010,0
69733	4 G 95	3/0	47,0	3648,0	6104,0
69734	5 G 95	3/0	52,5	4560,0	7891,0
69735	3 G 120	4/0	46,0	3456,0	5940,0
69736	4 G 120	4/0	51,5	4608,0	7604,0
69737	5 G 120	4/0	56,5	5760,0	8751,0

Dimensions and specifications may be changed without prior notice.

F



Our Service on the Internet:

Metal prices

On our Internet site, you will find the current metal prices for copper, brass, lead and aluminium as well as DEL prices developments and the dollar prices over the last few months.

www.helukabel.de