








































Contents

Description	Page
UL-Style 1007, CSA TR 64 , PVC single cores, 80°C, 300V	  F 4
UL-Style 1569, CSA TR 64 , PVC single cores, 105°C, 300V	  F 5
UL-Style 1015 , PVC single core, 600V	  F 6
THREENORM , PVC single core, UL-Style 1011 and CSA 600V	   F 7
FIVENORM , HAR-UL-CSA-AWM-MTW, PVC single core, UL-Style 1015/UL-Standard 1063, 600V, 105°C	   F 9
THHN/THWN , 90°C, 600V, UL listed, PVC + nylon single core	 F 11
HELUTHERM® 145 , 300V, flexible single core, electron beam cross-linked, halogen-free	  F 12
HELUTHERM® 145 , 600V, flexible single core, electron beam cross-linked, halogen-free	  F 13
Command Cable UL (LiYY) , Style 2464/300 V, (80°C)	  F 14
Command Cable UL (LiYY) , 600V, Style 2516/600 V, (105°C)	  F 15
Command Cable UL (LiYCY) , Style 2464, 300V, 80°C, EMC-preferred type	  F 16
Command Cable UL (LiYCY) , Style 2516/600 V, 105°C, EMC-preferred type	  F 18
Command Cable UL (LiYY-TP) , Style 2464/300V, 80°C	 F 19
Command Cable UL (LiYCY-TP) , Style 2464/300 V, 80°C, EMC-preferred type	  F 21
Rubber / Neoprene Control Cable , Types SJO und SO	  F 23
PVC Single Core , to CEI 20-22 II	 F 24
FROR CEI 20-22 II , empty	 F 25
C.N.O.M.O , Type NOV5-F according to NFC 32-207	 F 26
JZ 604 TC TRAY CABLE , PVC power cable, 90°C, 600V	  F 27
JZ 604-FCY TC TRAY CABLE , PVC power cable, screened, 90°C, 600V, EMC-preferred type	  F 29
JZ 604-YCY TC TRAY CABLE , PVC power cable, screened, 90°C, 600V, EMC-preferred type	  F 30