

N2XCH-FE 180/E 30 security cable, halogen-free, 0,6/1 kV, with improved fire characteristics



| Part No. | No. cores x cross-sec. mm² | Outer ø ca. mm | Cop. weight kg / km | Weight ca. kg / km | AWG-No. |
|----------|----------------------------|----------------|---------------------|--------------------|-----------|
| 52103 | 3 x 1,5 / 1,5 re | 13,0 | 66,0 | 220,0 | 16 |
| 52104 | 3 x 2,5 / 2,5 re | 14,0 | 104,0 | 270,0 | 14 |
| 52105 | 3 x 4 / 4 re | 15,5 | 161,0 | 360,0 | 12 |
| 52106 | 3 x 6 / 6 re | 16,5 | 240,0 | 470,0 | 10 |
| 52107 | 3 x 10 / 10 re | 18,5 | 408,0 | 680,0 | 8 |
| 52108 | 3 x 16 / 16 re | 21,0 | 643,0 | 960,0 | 6 |
| 52109 | 3 x 25 / 16 rm | 25,5 | 902,0 | 1390,0 | 4 |
| 52110 | 3 x 35 / 16 rm | 29,0 | 1190,0 | 1720,0 | 2 |
| 52111 | 3 x 50 / 25 rm | 31,5 | 1723,0 | 2320,0 | 1 |
| 52112 | 3 x 70 / 35 rm | 36,5 | 2410,0 | 3260,0 | 2/0 |
| 52113 | 3 x 95 / 50 rm | 40,0 | 3296,0 | 4310,0 | 3/0 |
| 52114 | 3 x 120 / 70 rm | 46,0 | 4236,0 | 5520,0 | 4/0 |
| 52115 | 3 x 150 / 70 rm | 50,5 | 5100,0 | 6620,0 | 300 kcmil |
| 52116 | 3 x 185 / 95 rm | 55,0 | 6383,0 | 8180,0 | 350 kcmil |
| 52117 | 3 x 240 / 120 rm | 61,5 | 8242,0 | 10620,0 | 500 kcmil |
| 52118 | 4 x 1,5 / 1,5 re | 15,0 | 81,0 | 260,0 | 16 |
| 52119 | 4 x 2,5 / 2,5 re | 16,0 | 128,0 | 310,0 | 14 |

| Part No. | No. cores x cross-sec. mm² | Outer ø ca. mm | Cop. weight kg / km | Weight ca. kg / km | AWG-No. |
|----------|----------------------------|----------------|---------------------|--------------------|-----------|
| 52120 | 4 x 4 / 4 re | 17,0 | 200,0 | 420,0 | 12 |
| 52121 | 4 x 6 / 6 re | 18,0 | 297,0 | 540,0 | 10 |
| 52122 | 4 x 10 / 10 re | 20,0 | 504,0 | 800,0 | 8 |
| 52123 | 4 x 16 / 16 re | 22,5 | 796,0 | 1150,0 | 6 |
| 52124 | 4 x 25 / 16 rm | 28,0 | 1142,0 | 1670,0 | 4 |
| 52125 | 4 x 35 / 16 rm | 30,5 | 1526,0 | 2160,0 | 2 |
| 52126 | 4 x 50 / 25 rm | 32,0 | 2203,0 | 2860,0 | 1 |
| 52127 | 4 x 70 / 35 rm | 39,5 | 3082,0 | 3980,0 | 2/0 |
| 52128 | 4 x 95 / 50 rm | 43,5 | 4208,0 | 5300,0 | 3/0 |
| 52129 | 4 x 120 / 70 rm | 49,5 | 5388,0 | 6740,0 | 4/0 |
| 52130 | 4 x 150 / 70 rm | 55,5 | 6558,0 | 8210,0 | 300 kcmil |
| 52131 | 4 x 185 / 95 rm | 60,0 | 8159,0 | 10200,0 | 350 kcmil |
| 52132 | 4 x 240 / 120 rm | 68,0 | 10546,0 | 12900,0 | 500 kcmil |
| 52133 | 7 x 1,5 / 2,5 re | 16,5 | 133,0 | 360,0 | 16 |
| 52134 | 30 x 1,5 / 6 re | 29,0 | 499,0 | 1070,0 | 16 |

Dimensions and specifications may be changed without prior notice.

letter

HELU - Newsletter

Use our HELU-Newsletter, to receive actual special prices.

Newsletter-subscription:

Email-address*:

Salutation:

First name:

Last name*:

HELU-client-no.:

Format: ☒ Html ☐ Text

The submitted data will only be used to personalise t

To cancel the HELU-Newsletter, subscribe your ema

Email-address*:

Our Service on the Internet:

HELU Newsletter

Take advantage of our HELU Newsletter service:
It's free and without obligation.
We report on HELUKABEL's broad
product spectrum, such as new products,
trade fairs, industry news and much more.

www.helukabel.de