



Technical data

- PVC-control cables to DIN VDE 0281 part 5 and IEC 60227-5, HD 21.5 S3
- **Temperature range**
flexing -5°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage**
U₀/U 300/500 V
- Max. permissible **operating voltage**
in three-phase and one-phase
a.c. system U₀/U 318/550 V
in direct current system
U₀/U 413/825 V
- **Test voltage** 2000 V
- **Breakdown voltage**
min. 4000 V
- **Insulation resistance**
min. 20 MΩm x km
- **Minimum bending radius**
flexing 7,5x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable construction

- Bare copper, fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5, BS 6360 cl. 5, IEC 60228 cl. 5 and HD 383
- PVC core insulation T12 to DIN VDE 0281 part 1
- Cores colour coded to DIN VDE 0293-308 1x green-yellow earth core incl.
- Green-yellow earth core, 3 cores and above
- Cores stranded in layers with optimal lay-length
- PVC outer jacket in white or black
- PVC outer jacket TM2 to DIN VDE 0281 part 1

Properties

- PVC self-extinguishing and flame retardant according to DIN VDE 0482 part 265-2-1/ EN 50265-2-1/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- G = with green-yellow earth core;
x = without green-yellow earth core.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- These types are also available with UL-approbation.
- The above list contains a selection of the types we carry in stock.
Other sizes available on request.
- Cables with 7 cores are only available as "A"-type.
- 6 mm² in adaption (H).

Application

These cables are especially suited to use for the appliance with medium mechanical stress in households, kitchens and offices, also for household appliances in damp and wet areas, e.g. refrigerators, washing machines, spin-driver etc. As far as this cable is admitted to the relevant specifications of the equipment.

These cables are suited to be used for cooking and heating apparatus under the condition that cable does not come in direct contact with hot parts of the apparatus and no other influences of heat.

The cables are suitable for fixed installation in furnitures, partition walls, decoration covering and in hollow spaces of prefabricated building parts.

They are not qualified for use in outdoors or for use with industrial and farmer machineries, exceptionally in tailoring, etc.

CE = The product is conformed with the EC Low-Voltage Directive 73/23/EEC and 93/68/EEC.

Part No.	No. cores x cross-sec. mm ²	Jacket colour	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
29450	2 x 0,75	black	6,4	14,4	50,0	18
29451	2 x 0,75	white	6,4	14,4	50,0	18
29452	3 G 0,75	black	6,8	21,6	60,0	18
29453	3 G 0,75	white	6,8	21,6	60,0	18
29454	4 G 0,75	black	7,4	29,0	73,0	18
29455	4 G 0,75	white	7,4	29,0	73,0	18
29456	5 G 0,75	black	8,3	36,0	88,0	18
29457	5 G 0,75	white	8,3	36,0	88,0	18
29458	2 G 1	black	6,8	19,0	57,0	17
29459	2 G 1	white	6,8	19,0	57,0	17
29460	3 G 1	black	7,2	29,0	73,0	17
29461	3 G 1	white	7,2	29,0	73,0	17
29462	4 G 1	black	8,0	38,0	85,0	17
29463	4 G 1	white	8,0	38,0	85,0	17
29464	5 G 1	black	8,8	48,0	105,0	17
29465	5 G 1	white	8,8	48,0	105,0	17
29466	7 G 1	black	9,8	67,0	131,0	17
29467	7 G 1	white	9,8	67,0	131,0	17
29484	2 G 1,5	black	7,6	29,0	82,0	16
29485	2 G 1,5	white	7,6	29,0	82,0	16
29486	3 G 1,5	black	8,2	43,0	95,0	16
29469	3 G 1,5	white	8,2	43,0	95,0	16
29470	4 G 1,5	black	9,2	58,0	117,0	16
29471	4 G 1,5	white	9,2	58,0	117,0	16

Part No.	No. cores x cross-sec. mm ²	Jacket colour	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
29472	5 G 1,5	black	9,3	72,0	144,0	16
29473	5 G 1,5	white	9,3	72,0	144,0	16
29474	7 G 1,5	black	10,8	101,0	183,0	16
29475	7 G 1,5	white	10,8	101,0	183,0	16
29478	3 G 2,5	black	10,1	72,0	152,0	14
29479	3 G 2,5	white	10,1	72,0	152,0	14
29480	4 G 2,5	black	11,2	96,0	192,0	14
29481	4 G 2,5	white	11,2	96,0	192,0	14
29482	5 G 2,5	black	12,4	120,0	243,0	14
29483	5 G 2,5	white	12,4	120,0	243,0	14
29486	7 G 2,5	black	12,9	168,0	316,0	14
29487	7 G 2,5	white	12,9	168,0	316,0	14
29825	3 G 4	black	11,3	115,0	235,0	12
29826	3 G 4	white	11,3	115,0	235,0	12
29488	4 G 4	black	12,5	154,0	300,0	12
29489	4 G 4	white	12,5	154,0	300,0	12
29490	5 G 4	black	13,7	192,0	361,0	12
29491	5 G 4	white	13,7	192,0	361,0	12
29492	4 G 6	black	13,9	230,0	490,0	10
29493	4 G 6	white	13,9	230,0	490,0	10

Dimensions and specifications may be changed without prior notice.