

N2XSY 6/10kV, 12/20kV, 18/30kV **XLPE-insulated,** Cu-conductor, single core, screened, PVC-jacket



Part No.	No. cores x cross-sec. mm²		Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Jacket thickness mm	Outer ø min - max mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
32428	1 x 50	rm / 16	36	18 / 30	8,0	2,5	33,0 - 38,0	662,0	1480,0	1
32429	1 x 70	rm / 16	36	18 / 30	8,0	2,5	35,0 - 40,0	854,0	1730,0	2/0
32430	1 x 95	rm / 16	36	18 / 30	8,0	2,5	36,0 - 41,0	1094,0	2060,0	3/0
32431	1 x 120	rm / 16	36	18 / 30	8,0	2,5	38,0 - 43,0	1334,0	2330,0	4/0
32432	1 x 150	rm / 25	36	18 / 30	8,0	2,5	39,0 - 44,0	1723,0	2720,0	300 kcmil
32433	1 x 185	rm / 25	36	18 / 30	8,0	2,5	41,0 - 46,0	2059,0	3100,0	350 kcmil
32434	1 x 240	rm / 25	36	18 / 30	8,0	2,5	43,0 - 48,0	2587,0	3730,0	500 kcmil
32435	1 x 300	rm / 25	36	18 / 30	8,0	2,5	46,0 - 51,0	3163,0	4000,0	600 kcmil
32436	1 x 400	rm / 35	36	18 / 30	8,0	2,5	49,0 - 54,0	4234,0	5330,0	750 kcmil
32437	1 x 500	rm / 35	36	18 / 30	8,0	2,5	52,0 - 57,0	5194,0	6480,0	1000 kcmil

Dimensions and specifications may be changed without prior notice.

Cable glands accessories

Locknuts
EMV locknuts
Fastening angle
Adapter
Extension / Reduction
Blanking plug
Screw caps
Seals



**You can find cable glands accessories in our cataloge cable accessories.
Request it now at www.helukabel.de**

