

NA2XSy 6/10kV, 12/20kV, 18/30kV XLPE-insulated, alu-conductor, single core, screened, PVC-jacket



Part No.	No. cores x cross-sec. mm ²	Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Jacket thickness mm	Outer ø min - max mm	Cop. weight kg / km	Alu weight kg / km	Weight ca. kg / km	AWG-No.	
32466	1 x 50	rm / 16	36	18 / 30	8,0	2,5	33,0 - 38,0	182,0	145,0	1260,0	1
32467	1 x 70	rm / 16	36	18 / 30	8,0	2,5	35,0 - 40,0	182,0	203,0	1360,0	2/0
32468	1 x 95	rm / 16	36	18 / 30	8,0	2,5	36,0 - 41,0	182,0	276,0	1510,0	3/0
32469	1 x 120	rm / 16	36	18 / 30	8,0	2,5	38,0 - 43,0	182,0	348,0	1610,0	4/0
32471	1 x 150	rm / 25	36	18 / 30	8,0	2,5	39,0 - 44,0	283,0	435,0	1810,0	300 kcmil
32470	1 x 150	rm / 16	36	18 / 30	8,0	2,5	39,0 - 44,0	182,0	435,0	1760,0	300 kcmil
32472	1 x 185	rm / 16	36	18 / 30	8,0	2,5	41,0 - 46,0	182,0	537,0	1960,0	350 kcmil
32473	1 x 185	rm / 25	36	18 / 30	8,0	2,5	41,0 - 46,0	283,0	537,0	2020,0	350 kcmil
32475	1 x 240	rm / 25	36	18 / 30	8,0	2,5	43,0 - 48,0	283,0	696,0	2260,0	500 kcmil
32474	1 x 240	rm / 16	36	18 / 30	8,0	2,5	43,0 - 48,0	182,0	696,0	2210,0	500 kcmil
32476	1 x 300	rm / 25	36	18 / 30	8,0	2,5	46,0 - 51,0	283,0	870,0	2560,0	600 kcmil
32477	1 x 400	rm / 35	36	18 / 30	8,0	2,5	49,0 - 54,0	394,0	1160,0	2960,0	750 kcmil
32478	1 x 500	rm / 35	36	18 / 30	8,0	2,6	52,0 - 57,0	394,0	1450,0	3460,0	1000 kcmil

Dimensions and specifications may be changed without prior notice.

Protective tubes

HELUcond protective tubes

Divisible protective HELUcond CO

Tubes made of metal / Anaconda protective tubes

Tube connectors

HELUTOP® Fast Clamp cable gland / circlip pliers

Divisible tubes

Protective tubes distributor

Tubing clamp

HELUcond Jumbosystem

Termination



You can find protective tubes in our catalogue cable accessories.
Request it now at www.helukabel.de