

NA2XS(F)2Y 6/10kV, 12/20kV, 18/30kV

XLPE-insulated, alu-conductor, single core, longitudinally water-tight, screened, PVC-jacket



Part No.	No.cores x cross-sec. mm²		Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Screen cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Alu weight kg / km	Weight ca. kg / km	AWG-No.
32621	1 x 50	rm / 16	36	18 / 30	8,0	16,0	37,0	182,0	145,0	1250,0	1
32622	1 x 70	rm / 16	36	18 / 30	8,0	16,0	38,0	182,0	203,0	1500,0	2/0
32623	1 x 95	rm / 16	36	18 / 30	8,0	16,0	40,0	182,0	276,0	1700,0	3/0
32624	1 x 120	rm / 16	36	18 / 30	8,0	16,0	42,0	182,0	348,0	1800,0	4/0
32625	1 x 150	rm / 25	36	18 / 30	8,0	25,0	43,0	283,0	435,0	2050,0	300 kcmil
32626	1 x 185	rm / 25	36	18 / 30	8,0	25,0	45,0	283,0	537,0	2150,0	350 kcmil
32627	1 x 240	rm / 25	36	18 / 30	8,0	25,0	47,0	283,0	696,0	2400,0	500 kcmil
32628	1 x 300	rm / 25	36	18 / 30	8,0	25,0	50,0	283,0	870,0	2700,0	600 kcmil
32629	1 x 400	rm / 35	36	18 / 30	8,0	35,0	53,0	394,0	1160,0	3200,0	750 kcmil
32630	1 x 500	rm / 35	36	18 / 30	8,0	35,0	56,0	394,0	1450,0	3550,0	1000 kcmil

Dimensions and specifications may be changed without prior notice.

Bunding, binding and fixing

Plastic spirals

Cable binders

Fixing mounting blocks

Velcro fastener binders

You can find bunding, binding and fixing in our catalogue cable accessories.
Request it now at www.helukabel.de