

N2XS2Y 6/10kV, 12/20kV, 18/30kV XLPE-insulated, Cu-conductor, single core, screened, PVC-jacket



Part No.	No. cores x cross-sec. mm²		Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Jacket thickness mm	Outer ø min - max mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
32508	1 x 50	rm / 16	36	18 / 30	8,0	2,5	33,0 - 38,0	662,0	1410,0	1
32509	1 x 70	rm / 16	36	18 / 30	8,0	2,5	35,0 - 40,0	854,0	1660,0	2/0
32510	1 x 95	rm / 16	36	18 / 30	8,0	2,5	36,0 - 41,0	1094,0	1970,0	3/0
32511	1 x 120	rm / 16	36	18 / 30	8,0	2,5	38,0 - 43,0	1334,0	2220,0	4/0
32512	1 x 150	rm / 25	36	18 / 30	8,0	2,5	39,0 - 44,0	1723,0	2650,0	300 kcmil
32513	1 x 185	rm / 25	36	18 / 30	8,0	2,5	41,0 - 46,0	2059,0	2980,0	350 kcmil
32514	1 x 240	rm / 25	36	18 / 30	8,0	2,5	43,0 - 48,0	2587,0	3570,0	500 kcmil
32515	1 x 300	rm / 25	36	18 / 30	8,0	2,5	46,0 - 51,0	3163,0	4220,0	600 kcmil
32516	1 x 400	rm / 35	36	18 / 30	8,0	2,5	49,0 - 54,0	4234,0	5170,0	750 kcmil
32517	1 x 500	rm / 35	36	18 / 30	8,0	2,5	52,0 - 57,0	5194,0	6260,0	1000 kcmil

Dimensions and specifications may be changed without prior notice.

Drag and guidance chains

EFK Series open:

10.1 / 14 / 18.1 / 18.2 / 35 / 3000 / 44 / 52.2 / 62.2

EFK Series closed: 25G / 36G

Chain brackets / separators

Filing systems / insertion aid

Assembly instruction

Selection table / Cables in drag chains



**You can find drag and guidance chains in our catalogue cable accessories.
Request it now at www.helukabel.de**