

N2XS(F)2Y 6/10kV, 12/20kV, 18/30kV

XLPE-insulated, Cu-conductor, single core, longitudinally water-tight, screened, PVC-jacket



Part No.	No.cores x cross-sec. mm²		Operation voltage max.	Nominal voltage kV	Insulation thickness mm	Screen cross-sec. mm²	Jacket thickness mm	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
32582	1 x 50	rm / 16	36	18 / 30	8,0	16,0	2,5	37,0	662,0	1700,0	1
32583	1 x 70	rm / 16	36	18 / 30	8,0	16,0	2,5	38,0	854,0	1950,0	2/0
32584	1 x 95	rm / 16	36	18 / 30	8,0	16,0	2,5	40,0	1094,0	2300,0	3/0
32585	1 x 120	rm / 16	36	18 / 30	8,0	16,0	2,5	42,0	1334,0	2600,0	4/0
32586	1 x 150	rm / 25	36	18 / 30	8,0	25,0	2,5	43,0	1723,0	3000,0	300 kcmil
32587	1 x 185	rm / 25	36	18 / 30	8,0	25,0	2,5	45,0	2059,0	3350,0	350 kcmil
32588	1 x 240	rm / 25	36	18 / 30	8,0	25,0	2,5	47,0	2587,0	4100,0	500 kcmil
32589	1 x 300	rm / 25	36	18 / 30	8,0	25,0	2,5	50,0	3163,0	4800,0	600 kcmil
32590	1 x 400	rm / 35	36	18 / 30	8,0	35,0	2,5	53,0	4234,0	5750,0	750 kcmil
32591	1 x 500	rm / 35	36	18 / 30	8,0	35,0	2,5	56,0	5194,0	6700,0	1000 kcmil

Dimensions and specifications may be changed without prior notice.

Termination and connection sleeves

Straight low voltage / high voltage

Indoor terminations

Outdoor terminations

Core connectors for telephone and signal cables

Accessories for mean voltage

You can find termination and connection sleeves in our cataloge cable accessories.
Request it now at www.helukabel.de