











Contents

| Description | Page |
|--|------|
| BAUFLEX , the universal cable | 0 4 |
| YELLOWFLEX , cold flexible, robust | 0 5 |
| NEOPREN Command Cable , flexible, colour or number coded | 0 6 |
| LIFT-TRAGO-30 / -60 , lift hoist control cable, pendal length 30 m bzw 60 m | 0 7 |
| TRAGO / Lift-2S , Lift and Hoist Control Cables 300/500V | 0 8 |
| TROMM-PUR-H , PUR trailing, halogen-free  | 0 9 |
| TROMM-PUR , PUR trailing and control cable, halogen-free | 0 10 |
| NSHTÖU , drum cable, VDE approved | 0 11 |
| H05 RR-F / H05 RN-F , rubber-sheathed cable, VDE approved  | 0 12 |
| H07 RN-F , rubber-sheathed cable, harmonized type  | 0 13 |
| A07 RN-F , rubber-sheathed cable, authorised national type  | 0 15 |
| H07 ZZ-F , control cable, cross linked, halogen-free  | 0 16 |
| NSSHÖU , heavy duty rubber cable for mining working, 0,6/1kV | 0 18 |
| H05G-U / -K / H07G-U / -R / -K  | 0 19 |
| Tauchflex-R , 750V, blue, submersible-pump cable | 0 20 |
| H07 RN8-F , rubber-sheathed cable, harmonized type  | 0 21 |
| Tauchflex-FL , 750 V, blue, submersible pump cable | 0 23 |
| NSGAFÖU 3kV , Special Rubber-Insulated Cable, VDE approved, short-circuit up to 1000V  | 0 24 |
| NSHXAFÖ 3kV , halogen-free Special Rubber-Insulated Cable, VDE approved, short-circuit up to 1000V  | 0 25 |
| H01N2-D / -E , 100 V, VDE approved, (NSLFFÖU), welding cable  | 0 26 |