



## Technical data

- Rubber sheathed cable H07 RN-F to DIN VDE 0282 part 4, HD 22.4 S3  $\Delta$  IEC 60245-4
- **Temperature range**  
-30°C to +60°C
- Permissible **operating temperature** at conductor +60°C
- **Nominal voltage**  $U_0/U$  450/750 V in case of protected and fixed installation  $U_0/U$  600/1000 V
- Max. permissible **operating voltage** in three phase and one phase a.c. system  $U_0/U$  476/825 V direct current-system  $U_0/U$  619/1238 V
- **Test voltage** 2500 V
- **Permanent tensile load**  
max. 15 N/mm<sup>2</sup>
- **Minimum bending radius**  
for fixed installation 4x cable  $\varnothing$   
for guiding over roller 7,5x cable  $\varnothing$   
during winding on drums 5-7x cable  $\varnothing$

## Cable construction

- Copper conductor fine wire stranded, bare or tinned to DIN VDE 0295 cl. 5, BS 6360 cl. 5, IEC 60228 cl. 5 and HD 383
- Rubber core insulation EI4 to DIN VDE 0282 part 1
- Insulation thickness to DIN VDE 0282 part 4
- Core identification to DIN VDE 0293-308 and HD 186
- Core colours  
up to 5 cores one-coloured  
6 and more cores, black with numbering  
3 and above, with green-yellow earth core  
2 cores without green-yellow earth core
- Cores stranded in layers with optimal lay-length
- Outer jacket of rubber black, rubber compound to DIN VDE 0282 part 1
- Sheath thickness to DIN VDE 0282 part 4

## Properties

- **Resistant to**  
Ozone  
Weather
- **Oil resistant**  
Test according to EN 60811-2-1
- **Test of behaviour compared to environmental influences**  
Test according to DIN VDE 0482 part 265-2-1/ EN 50265-2-1/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)  
Ozone resistant of the insulation to DIN VDE 0472 part 805, test method A or part 805 A1, test method C
- The core identification of a single core jacketed, of an insulated wire is black. For application as a protective core, the ends are to be identified with green-yellow and the middle conductor with light blue

## Note

- G = with green-yellow earth core;  
x = without green-yellow earth core.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- Further dimensions and cross-sections available on request.
- H07 RN-F = harmonized rubber-sheathed cable, working voltage 750 V, fine stranded.

## Application

Heavy duty rubber-sheathed flexible cables are suited for use for medium mechanical stress in dry, damp and wet areas as well as in open air and in agriculture plants.

They are used for equipment in industry works such as boilers, heating plates, hand lamps, electric tools such as drills, circular saws and homework tools as well as for transportable motors or machines at site.

These cables are also suitable for fixed installation on plaster, in temporary buildings and residential barracks. They are suitable for direct laying on components and mechanical parts of machines, for example lifts and cranes.

They can be used in case of protected and fixed installation in tubes or in equipment as well as rotor connecting cable of motors with a working voltage up to 1000 V alternating voltage or a direct voltage up to 750 V against ground. The operating direct voltage is permitted up to 900 V against ground when they are used in rail-coaches. Installation in hazardous areas according to DIN VDE 0165 is allowed.

CE = The product is conformed with the EC Low-Voltage Directive 73/23/EEC and 93/68/EEC.

Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer $\varnothing$ ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
37001	1 x 1,5	5,7 - 7,1	14,4	58,0	16
37002	1 x 2,5	6,3 - 7,9	24,0	71,0	14
37003	1 x 4	7,2 - 9,0	38,0	100,0	12
37004	1 x 6	7,9 - 9,8	58,0	130,0	10
37005	1 x 10	9,5 - 11,9	96,0	230,0	8
37006	1 x 16	10,8 - 13,4	154,0	290,0	6
37007	1 x 25	12,7 - 15,8	240,0	420,0	4
37008	1 x 35	14,3 - 17,9	336,0	530,0	2
37009	1 x 50	16,5 - 20,6	480,0	750,0	1
37010	1 x 70	18,6 - 23,3	672,0	960,0	2/0
37011	1 x 95	20,8 - 26,0	912,0	1250,0	3/0
37012	1 x 120	22,8 - 28,6	1152,0	1560,0	4/0
37013	1 x 150	25,2 - 31,4	1440,0	1900,0	300 kcmil
37014	1 x 185	27,6 - 34,4	1776,0	2300,0	350 kcmil
37015	1 x 240	30,6 - 38,3	2304,0	2950,0	500 kcmil
37016	1 x 300	33,5 - 41,9	2880,0	3600,0	600 kcmil
37017	1 x 400	37,4 - 46,8	3840,0	4600,0	750 kcmil
37018	1 x 500	41,3 - 52,0	4800,0	6000,0	1000 kcmil

Part No.	No. cores x cross-sec. mm <sup>2</sup>	Outer $\varnothing$ ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
37019	2 x 1	7,7 - 10,0	19,0	98,0	17
37020	2 x 1,5	8,5 - 11,0	29,0	135,0	16
37021	2 x 2,5	10,2 - 13,1	48,0	193,0	14
37022	2 x 4	11,8 - 15,1	77,0	280,0	12
37023	2 x 6	13,1 - 16,8	115,0	330,0	10
37024	2 x 10	17,7 - 22,6	192,0	586,0	8
37025	2 x 16	20,2 - 25,7	307,0	810,0	6
37026	2 x 25	24,3 - 30,7	480,0	1160,0	4
37027	3 G 1	8,3 - 10,7	29,0	130,0	17
37028	3 G 1,5	9,2 - 11,9	43,0	165,0	16
37029	3 G 2,5	10,9 - 14,0	72,0	235,0	14
37030	3 G 4	12,7 - 16,2	115,0	320,0	12
37031	3 G 6	14,1 - 18,0	173,0	420,0	10
37032	3 G 10	19,1 - 24,2	288,0	810,0	8
37033	3 G 16	21,8 - 27,6	461,0	1050,0	6
37034	3 G 25	26,1 - 33,0	720,0	1250,0	4
37035	3 G 35	29,3 - 37,1	1008,0	1900,0	2
37036	3 G 50	34,1 - 42,9	1440,0	2600,0	1