


H07 RN8-F rubber-sheathed cable, harmonized type



Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.	Part No.	No. cores x cross-sec. mm ²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
37330	4 G 1	9,2 - 11,9	38,0	150,0	17	37354	5 G 1	10,2 - 13,1	48,0	175,0	4
37331	4 G 1,5	10,2 - 13,1	58,0	200,0	16	37347	5 G 1,5	11,2 - 14,4	72,0	240,0	16
37332	4 G 2,5	12,1 - 15,5	96,0	290,0	14	37348	5 G 2,5	13,3 - 17,0	120,0	345,0	14
37333	4 G 4	14,0 - 17,9	154,0	395,0	12	37349	5 G 4	15,6 - 19,9	192,0	485,0	12
37334	4 G 6	15,7 - 20,0	230,0	540,0	10	37350	5 G 6	17,5 - 22,2	288,0	650,0	10
37335	4 G 10	20,9 - 26,5	384,0	950,0	8	37351	5 G 10	22,9 - 29,1	480,0	1200,0	8
37336	4 G 16	23,8 - 30,1	614,0	1260,0	6	37352	5 G 16	26,4 - 33,3	768,0	1550,0	6
37337	4 G 25	28,9 - 36,6	960,0	1860,0	4	37353	5 G 25	32,0 - 40,4	1200,0	2250,0	4
37338	4 G 35	32,5 - 41,1	1344,0	2380,0	2	37355	6 G 1,5	13,4 - 17,2	87,0	171,0	4
37339	4 G 50	37,7 - 47,5	1920,0	3190,0	1	37356	6 G 2,5	15,7 - 20,0	144,0	279,0	4
37340	4 G 70	42,7 - 54,0	2688,0	4260,0	2/0	37357	12 G 1,5	17,6 - 22,4	173,0	340,0	4
37341	4 G 95	48,4 - 61,0	3648,0	5600,0	3/0	37358	12 G 2,5	20,6 - 26,2	288,0	571,0	4
37342	4 G 120	53,0 - 66,0	4608,0	6830,0	4/0						
37343	4 G 150	58,0 - 73,0	5760,0	8320,0	300 kcmil						
37344	4 G 185	64,0 - 80,0	7104,0	9800,0	350 kcmil						
37345	4 G 240	72,0 - 91,0	9216,0	12100,0	500 kcmil						
37346	4 G 300	80,0 - 101,0	11520,0	15200,0	600 kcmil						

Dimensions and specifications may be changed without prior notice.



Our Service on the Internet:

HELU Newsletter

Take advantage of our HELU Newsletter service: It's free and without obligation. We report on HELUKABEL's broad product spectrum, such as new products, trade fairs, industry news and much more.

www.helukabel.de