


H07 ZZ-F control cable, cross linked, halogen-free



Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
37229	4 G 70	42,7 - 54,0	2688,0	4130,0	2/0
37230	4 G 95	48,4 - 61,0	3648,0	5720,0	3/0
37231	4 G 120	53,0 - 66,0	4608,0	6965,0	4/0
37232	4 G 150	58,0 - 73,0	5760,0	8644,0	300 kcmil
37233	4 G 185	64,0 - 80,0	7104,0	10598,0	350 kcmil
37234	4 G 240	72,0 - 91,0	9216,0	12100,0	500 kcmil
37235	4 G 300	80,0 - 101,0	11520,0	15200,0	600 kcmil
37236	5 G 1	10,2 - 13,1	48,0	170,0	17
37237	5 G 1,5	11,2 - 14,4	72,0	214,0	16
37238	5 G 2,5	13,3 - 17,0	120,0	316,0	14
37239	5 G 4	15,6 - 19,9	192,0	448,0	12
37240	5 G 6	17,5 - 22,2	288,0	607,0	10
37241	5 G 10	22,9 - 29,1	480,0	1075,0	8
37242	5 G 16	26,4 - 33,3	768,0	1480,0	6
37243	5 G 25	32,0 - 40,4	1200,0	2255,0	4
37244	6 G 1,5	13,4 - 17,2	84,0	287,0	16
37245	6 G 2,5	15,7 - 20,0	144,0	420,0	14
37246	6 G 4	18,2 - 23,2	230,0	583,0	12

Part No.	No. cores x cross-sec. mm²	Outer ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
37247	7 G 1,5	0,0 - 14,4	101,0	303,0	16
37248	7 G 2,5	0,0 - 17,0	168,0	448,0	14
37249	12 G 1,5	17,6 - 22,4	173,0	496,0	16
37250	12 G 2,5	20,6 - 26,2	288,0	724,0	14
37251	12 G 4	24,4 - 30,9	461,0	1042,0	12
37252	18 G 1,5	20,7 - 26,3	259,0	702,0	16
37253	18 G 2,5	24,4 - 30,9	432,0	1045,0	14
37254	18 G 4	28,8 - 36,4	691,0	1430,0	12
37255	24 G 1,5	24,3 - 30,7	346,0	935,0	16
37256	24 G 2,5	28,8 - 36,4	576,0	1325,0	14
37257	36 G 1,5	27,8 - 35,2	518,0	1297,0	16
37258	36 G 2,5	33,2 - 41,8	864,0	1949,0	14

Dimensions and specifications may be changed without prior notice.



Our Service on the Internet:

Catalogue, brochure and flyer requests

Here you can request catalogues, brochures and flyers or download them immediately as pdf-documents. Just click and order.



www.helukabel.de