



Technical data

- Special-crane-drum cable to DIN VDE 0250 part 814
- **Temperature range**
flexing -35°C to +70°C
fixed installation -40°C to +70°C
- Max. **conductor temperature**
under load +60°C
circuit conditions +200°C
- **Nominal voltage** U_0/U 0,6/1 kV
- Max. **permissible nominal voltages**
for three phase and one phase a.c.
current installation U_0/U 0,7/1,2 kV
for direct current U_0/U 0,9/1,8 kV
- **Test voltage** 2500 V
- **Insulation resistance**
min. 10 MΩm x km
- **Minimum bending radius**
10x cable Ø
- **Radiation resistance**
up to 20×10^6 cJ/kg (up to 20 Mrad)

Cable construction

- Tinned copper fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Rubber core insulation GI1 to DIN VDE 0207 part 20
- Core identification to DIN VDE 0293, 6 cores and above with numbering
- Cores stranded (without elongated central core) with max. lay-length of $8 \times \text{Ø}$ over the stranding layers
- Suspension strains as strain relieving elements
- Textile tape
- Textile braiding as protection against torsion, embedded in inner filling sheath
- Neoprene outer jacket, type 5GM2 to DIN VDE 0207 part 21
- Jacket colour black

Properties

- Designed and developed for trailing use
- Permissible running speed up to 120 m/min max.
- Polychloroprene-rubber (neoprene)-jacket, extremely cold resistant
- **Behaviour in fire**
Test according to DIN VDE 0482 part 265-2-1/ EN 50265-2-1/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- **Oil resistant**
Test according to VDE 0472 part 803, test method A
- Due to the neoprene outer jacket, the cables is **resistant against** ozone and radiation, oils, acids, fats, gasoline, solvents and chemicals
- During the installation and operation the tensile stress on conductor may not increase 15 N/mm²
- Acceleration not more than 0,4 m/sec²
- While using 1 to 2 convolutions should remain on the operated drum
- In case of high mechanical stress, especially of high dynamic tensile stress result high acceleration, the permissible stress must be defined in each case

Note

- G = with green-yellow earth core.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².

Application

Trailing cables are used for high mechanical stress, especially for applications with frequent winding and unwinding with simultaneous tensile and torsional stress, for building machinery, conveyors, shifts and cranes. They are used as robust and all weather resistant cables of roughest operations in mining and in flexible handling equipment and railway motors. The cables are suitable for outdoor installation in dry, damp and wet places.

CE= The product is conformed with the EC Low-Voltage Directive 73/23/EEC and 93/68/EEC.

Part No.	No. cores x cross-sec. mm ²	Outer Ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
26001	3 G 1,5	13,6	47,0	236,0	16
26029	4 G 1,5	14,0	58,0	274,0	16
26002	5 G 1,5	14,5	81,0	316,0	16
26003	7 G 1,5	18,8	115,0	440,0	16
26004	12 G 1,5	21,0	196,0	606,0	16
26005	16 G 1,5	24,5	259,0	696,0	16
26006	18 G 1,5	25,5	271,0	750,0	16
26007	24 G 1,5	27,5	390,0	1150,0	16
26008	30 G 1,5	29,5	432,0	1325,0	16
26009	3 G 2,5	15,3	74,0	305,0	14
26010	4 G 2,5	16,5	98,0	350,0	14
26011	5 G 2,5	17,5	124,0	465,0	14
26012	7 G 2,5	20,0	168,0	576,0	14
26013	12 G 2,5	23,5	308,0	850,0	14
26014	18 G 2,5	28,0	451,0	1181,0	14
26015	24 G 2,5	32,5	615,0	1550,0	14
26016	30 G 2,5	34,0	770,0	1810,0	14
26017	40 G 2,5	42,5	1080,0	3110,0	14
26018	50 G 2,5	46,5	1200,0	3200,0	14
26019	4 G 4	18,5	158,0	510,0	12
26030	5 G 4	21,5	220,0	635,0	12

Part No.	No. cores x cross-sec. mm ²	Outer Ø ca. mm	Cop. weight kg / km	Weight ca. kg / km	AWG-No.
26020	4 G 6	21,0	241,0	650,0	10
26031	5 G 6	23,5	317,0	800,0	10
26021	4 G 10	26,0	404,0	1010,0	8
26022	5 G 10	28,0	508,0	1200,0	8
26023	4 G 16	29,0	642,0	1300,0	6
26032	5 G 16	31,5	768,0	1700,0	6
26024	4 G 25	35,0	1005,0	2000,0	4
26025	4 G 35	37,5	1344,0	2610,0	2
26026	4 G 50	44,5	2010,0	3500,0	1
26027	4 G 70	49,0	2688,0	4600,0	2/0
26028	4 G 95	56,0	3648,0	6100,0	3/0

Dimensions and specifications may be changed without prior notice.